

DATA SHEET



15ft DisplayPort™ Male to Single Link DVI-D Male Adapter Cable - Black (TAA Compliant)

Directly connect a DisplayPort laptop to a DVI-D display for video

OVERVIEW

This DisplayPort to Single-Link DVI-D Adapter Cable is an easy and convenient solution for connecting a DVI-D monitor to a DisplayPort computer in your home or your office. This adapter cable carries a digital video signal, supports up to a 1920 x 1200 resolution and meets the requirements of high performance applications.

Avoid frustration by simply plugging the male DisplayPort into your computer and then plug the male DVI-D into your monitor or projector. The cable form factor of this adapter provides a simple and convenient solution that eliminates the need for a separate adapter and cable.

This adapter cable automatically converts the digital DisplayPort signal to Single-Link DVI-D, supporting full HD up to a 1920 x 1200 resolution.

FEATURES

- Supports legacy Single-Link DVI-D display devices, so no need to purchase a new monitor
- Plug-and-play, so no additional software or drivers needed
- Supports resolutions up to 1920 x 1200, for viewing your screen content at full HD

ITEM	DESCRIPTION
C2G54342	15ft DisplayPort Male to Single Link DVI-D Male Adapter Cable - Black (TAA Compliant)

DATA SHEET

SPECIFICATIONS:

DisplayPort Male to Single Link DVI-D Male Adapter Cable - Black (TAA Compliant)

ELECTRICAL SPECIFICATIONS:

- Voltage Rating: 30v
- Conductor Resistance: @ 20°C max
- Insulation Resistance: 10MΩ/km
- Time Delay: 5.2ns/m (max)
- Attenuation:
 - 5.02dB@100-450MHz 7.69dB@1GHz
 - 12.595dB@2GHz 17.495dB@3GHz
 - 22.395dB@4GHz 27.295dB@5GHz
 - 32.195dB@6GHz 37.095dB@7GHz

PHYSICAL SPECIFICATIONS:

- Operating Temperature: 0°C to 50°C
- Storage Temperature: -25°C to 70°C
- Approvals: CE

PHYSICAL CHARACTERISTICS:

Conductor (2 Conductors, 5 Pair):

- Conductor: 30AWG (7/0.1TC)
- Insulation: FM-PE, ID:0.8±0.05mm
- Color: White/Brown, White/Red, White/Orange, White/Green, White/Blue
- Drain: 30AWG (7/0.1TC) HD-PE ID:0.56±0.05
- Shield: AL-Mylar Wrap Coverage—100%

Conductor (5 Conductors):

- Conductor: 30AWG (7/0.1TC)
- Insulation: HD-PE, ID:0.56±0.05mm
- Color: Red/Orange/Yellow/Green/ White

Overall Cable

- Jacket: PVC
- Shield: AL-Mylar—Coverage 100% Braid—16/9/0.12
- Drain: 2:30AWG (7/0.08 BC)
- OD: 6.5±0.2

C2G®

A brand of  **legrand**®

UK (0)800 328 2916 EMEA +44 (0)1952 677300 w: www.c2g.com/uk

©2020 Legrand AV Inc. 200542 Rev A 8/20 C2G is a registered trademark of Legrand AV Inc. All rights reserved. All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All patents are protected under existing designations. Other patents pending.

COMMERCIAL BRANDS

C2G | Chief | Da-Lite | Luxul | Middle Atlantic | Vaddio | Wiremold